



L120R

## DTB-L120R Label

### Air Interface Protocol

EPC Global Class1 Gen2 ISO18000-6C

### Operational Frequency

Global 860-960MHz

### Tag Dimensions

230 \* 4.5 mm



Mechanical Parameters	
Base Material	PET
Face Material	80g Coated Paper
Liner	Release Paper
Quantity	5000 PCS / Roll (Can Be Customized)
Tag Pitch	12.14 mm
Reel Inner Diameter	76.2 mm
Tag Dimensions	230 * 4.5 mm
Antenna Dimensions	120 * 3 mm

Electrical Parameters	
Air Interface Protocol	EPC Global Class1 Gen2 ISO18000-6C
Frequency	Global 860-960MHz
IC Type	Impinj Monza R6-P (Can Be Customized)
Memory	EPC 96/128 bits;TID 96 bits;User :32/64 bits
IC Life	100,000 Times
Data Retention	10 Years
Application Surface	Non Metal Surface
Reading Range	About 5 m (US Standard, Handheld 1W)

Other Parameters	
Operating Temperature	-20°C ~ 80°C
Storage Temperature	20°C ~ 30°C
Storage Humidity	20 ~ 90 % Relative Humidity
Shelf Life	20°C ~ 30°C, 40 ~ 60% Relative Humidity, More Than 2 Years

